

Description One of the most durable and plentiful of the Vermont slates. A pleasure to work with for the slate craftsman—cuttable and consistent. This stone is grey/green when freshly quarried and a naturally harmonious blend of greens, greys and buff after weathering.

Origin Vermont

Lengths (inches)	Widths (inches)	Exposure (3" Headlap, inches)
24	12, 14	10.5
22	11, 12, 14	9.5
20	10, 11, 12	8.5
18	9, 10, 11, 12	7.5
16	8, 9, 10, 11, 12	6.5
14	7, 8, 9, 10, 11, 12	5.5
12	6, 7, 8, 9, 10, 12	4.5

Thickness (inches)	Pounds per Square
Nominal $1/4$ – $3/8$	850–950
$3/8$ – $1/2$	1,300–1,400
$1/2$ – $3/4$	1,800–2,100
$3/4$ –1	2,700–3,000
1– $1 1/4$	3,600–4,000

Please note that not all sizes are available in every thickness. Call for availability.

Slate General Properties

- 100% natural product
- Exceptionally durable, 100-year useful life
- Proven historic performance & beauty
- Non-combustible—Class A Fire Resistant
- Resistant to acid rain, ultra-violet light & chemicals
- Withstands freeze/thaw cycles & high temperatures
- Rated Class 3 and Class 4 Hail Impact Resistance ($3/4$ to 2 inch ice balls)

	This Slate*	ASTM Standards:
Breaking Load	582 pounds	575 pounds minimum
Water Absorption	0.151%	0.25% maximum
Depth of Softening	0.0019"	0.002" maximum
ASTM Rating	S1	

**As tested by ASTM. Test report available upon request.*

363 Vermont 30 South, Poultney, VT 05764

802-287-2295 | Fax 802-287-2296 | newenglandslate.com | Formed by Nature, Crafted by Hand